

DRUM PRE-CLEANER

DP1.15.1909.GB

DP-630 / -950



The DP drum pre-cleaner is above all used in intake sections and silos to relieve the following machines and conveyors

The DP separates coarse impurities such as paper, pieces of wood, maize leaves and cobs etc.

For capacity and all other specific information see the back page.

The DP drum pre-cleaner offers the below features:

- Inlet spout and inlet channel.

- Rotating horizontal drum with wire mesh.
- Guide spiral to convey the product to the outlet end.
- Scraper cleaning.
- Spout for dust aspiration.
- Fixed drive and motor.

The machine is of steel construction.

Options:

- *Additional drum*

EQUIPPED FOR CHANGE

We provide valuable insights, so you can make qualified decisions

DRUM PRE-CLEANER DP-630 / -950

TECHNICAL SPECIFICATIONS:

	DP-630	DP-950
Drum dia. x length mm	630 x 780	950 x 1080
Mesh opening mm	40 x 40*	40 x 40*
Drum area m ²	1.54	3.2
Motor kW	0.37	0.55
Capacity t/h	100	200

** Other sizes on request*

Capacity: estimate [guideline] based on wheat.

DISTINGUISHING ADVANTAGES:

- Completely closed unit
- Connection for external dust aspiration system
- Easy clean-down when changing from one product to another
- Low maintenance costs

